

**Feature Overview**

- RFID LF Desktop Reader
- Support LF standard protocol tag
- Small size and high performance
- Available with Software for demo and configuration
- Low-power dissipation design
- CE certified



**Applications**

- Data collection
- Asset Management
- Logistics
- Programmer




**Technical features**

Supported Transponder	Several types of LF 125 kHz transponders
Operation	Reader tag LF
Operating frequency	125Khz
Antenna	Integrated
Reading distance	10cm typ
Write distance	Solo lettura
Communication interface	USB
Power Supply	5Vcc (USB)
Power Current	90mA typ.
Signal	Led
Dimensions	104 x 68 x 10mm
Operating temperature	-20°C ÷ 60°C
Protection	IP40
Housing	ABS
Colour	Light grey

Notes:

**Models available**

P.N.	Type	Interface	Dimensions	Picture
AP403	EM4200 or similar Virt. Keyboard	USB	105 x 70 x 12mm	
AP401	EM4200 or similar	RS232	105 x 70 x 12mm	
AP405	HID format	USB	105 x 70 x 12mm	
AP402	EM4200 o similar	USB	105 x 70 x 12mm	



Notes:  
 Custom adjustment or firmware personalization available on every model.  
 Specifications are subject to change without prior notice.