

Feature Overview

- RFID LF and HF tag in keychain format
- ABS housing
- Black colour (also available with other color)
- Internal copper antenna available with different size
- Operating temperature: -20 +80°C
- Storage temperature: -20 +80°C
- Available in read only or read and write version
- Small size

Applications

- Contactless and automatic ID
- Access control
- Industrial automation
- Logistics
- Gyms
- Recreation centers
- Automatic machines



Mainly indicated for industrial and civil applications, automation machines and access control. Also available in different colour.

Models

Part Number	Frequency	Chip	Type	Diameter	Notes
601W029	125 kHz	EM4100	ro 64bit	36 X 30 X 7 mm	
691W029	125 kHz	TK4100	ro 64bit	36 X 30 X 7 mm	
602W029	125 kHz	EM4550	rw 1kbit	36 X 30 X 7 mm	
611W029	125 kHz	T5577	rw 330bit	36 X 30 X 7 mm	
607W029	13,56 MHz	MIFARE 1K	rw 1kbyte	36 X 30 X 7 mm	
629W029	13,56 MHz	I-CODE 2	rw 1kbit	36 X 30 X 7 mm	
693W029	13,56 MHz	K50 ISO14443A	rw 1kbyte	36 X 30 X 7 mm	

Information from manufacturer specifications.

Specifications are subject to change without prior notice.