

### Feature Overview

- RFID LF and HF tags family in bracelet format
- Antiallergic silicone housing
- Yellow, Blue, Red, Black and White colour
- Operating temperature: -25 +50°C
- Storage temperature: -25 +75°C
- 17 gram weight
- IP68 Protocol
- Internal copper antenna
- Central part size 32 X 25 X 6 mm
- (Size1 diameter 20cm - Size2 diameter 23cm)

### Applications

- Contactless and automatic ID
- Access control
- Gyms
- Recreations Center



RFID LF and HF tags family suitable for the automatic ID of people.

### Models

| Size1   | Size2   | Frequency | Chip       | Type      | Notes |
|---------|---------|-----------|------------|-----------|-------|
| 601W042 | 601W043 | 125 kHz   | EM4100     | ro 64bit  |       |
| 691W042 | 691W043 | 125 kHz   | TK4100     | ro 64bit  |       |
| 602W042 | 602W043 | 125 kHz   | EM4550     | rw 1kbit  |       |
| 611W042 | 611W043 | 125 kHz   | T5577      | rw 363bit |       |
| 608W042 | 608W043 | 125 kHz   | HITAG1     | rw 2kbit  |       |
| 607W042 | 607W043 | 13,56 MHz | MIFARE 1K  | rw 1kbyte |       |
| 629W042 | 629W043 | 13,56 MHz | I-CODE SLI | rw 1kbit  |       |
| 693W042 | 692W043 | 13,56 MHz | K50        | rw 1kbyte |       |

Also available with other chip.

Information from manufacturer specifications.

Specifications are subject to change without prior notice.